

MULTI SPLIT C1 wall-mounted air conditioners

TEMPERATURE SETPOINT from 16 to 30°C



High energy efficiency

Innovative solutions enabled a significant reduction of energy consumption in both cooling and heating mode. The appliances have A++/A+ energy rating.



Quick and easy installation

The design of the air conditioners and new technological solutions enable trouble-free and efficient installation. Easier access, increased installation space and right- and left-sided connection options reduce the installation time to as little as 40 min.



R32 refrigerant

The R32 refrigerant used in air conditioners makes them far more efficient than the appliances operating on the commonly used R410A refrigerant.




SMART airflow

An innovative solution for airflow control. The stream is directed upwards during the cooling and downwards during the heating, which enables an even distribution of air, thus preventing direct airflow on the user.



Quiet operation

The components comprising the air conditioner and the optimum airflow system ensure quiet operation for comfort during work and leisure.





Wireless controller
YR-HAC01 (included)



Indoor unit		JS050-C1	
Rated capacity	Cooling	kW	5.0
	Heating	kW	5.2
Electrical parameters	Power supply	f/V/Hz	1/230/50
Performance	Airflow	m ³ /h	900
	Sound power level	dB(A)	57
	Sound pressure level	dB(A)	44/40/35/28
Installation	Dimensions without packaging (W/D/H)	mm	1008/225/318
	Dimensions with packaging (W/D/H)	mm	1085/329/403
	Net/gross weight	kg	11.6/14.4
	Liquid pipe diameter	mm	6.35
	Gas pipe diameter	mm	12.7
	Controller	Standard	YR-HAC01