

MULTI SPLIT

Cassette air conditioners

with 4-way airflow

TEMPERATURE SETPOINT from 16 to 30°C



High energy efficiency

Innovative solutions enabled a significant reduction of energy consumption in both cooling and heating mode. The appliances have A++/A energy rating.



SMART airflow

An innovative solution for airflow control. The stream is directed upwards during the cooling and downwards during the heating, which enables an even distribution of air, thus preventing direct airflow on the user.




Airflow speed control

The option to control airflow shutters vertically enables precise direction of the airflow. The function is available from the controller.



Quiet operation

The components comprising the air conditioner and the optimum airflow system ensure quiet operation for comfort during work and leisure.





(option)



Wireless controller
YR-HRC01 (optional)



YR-C01
wired controller
(optional)



Indoor unit			CA035-A1	CA050-A1
Rated capacity	Cooling	kW	3.5	5
	Heating	kW	4.0	5.5
Electrical parameters	Power supply	f/V/Hz	1/220-240/50/60	1/220-240/50/60
Performance	Airflow	m ³ /h	620/520/420/350	700/600/500/400
	Sound power level	dB(A)	52	57
	Sound pressure level	dB(A)	35/32/30/28	42/37/35/31
Installation	Dimensions without packaging (W/D/H)	mm	570/570/260	570/570/260
	Dimensions with packaging (W/D/H)	mm	718/680/380	718/680/380
	Net/gross weight	kg	18.5/22	18.5/22
	Liquid pipe diameter	mm	6.35	6.35
	Gas pipe diameter	mm	9.52	12.7
Controller	Wireless option		YR-HRC01	YR-HRC01
	Wired option		YR-C01	YR-C01
Cover	Type	Option	PB-700HE4	PB-700HE4
	Dimensions without packaging (W/D/H)	mm	700/700/60	700/700/60
	Dimensions with packaging (W/D/H)	mm	740/750/115	740/750/115
	Net/gross weight	kg	2.8/4.8	2.8/4.8