


MULTI SPLIT

Cassette air conditioners

with peripheral airflow



TEMPERATURE SETPOINT from 16 to 30°C



Peripheral airflow

With the 360-degree cover, the air is supplied from four sides and corners to ensure efficient airflow in the room.



High energy efficiency

Innovative solutions enabled a significant reduction of energy consumption in both cooling and heating mode. The appliances have A++/A energy rating.



SMART airflow

An innovative solution for airflow control. The stream is directed upwards during the cooling and downwards during the heating, which enables an even distribution of air, thus preventing direct airflow on the user.




Airflow speed control

The option to control airflow shutters vertically and horizontally enables precise direction of the airflow. The function is available from the wireless controller.



Quiet operation

The components comprising the air conditioner and the optimum airflow system ensure quiet operation for comfort during work and leisure.



Indoor unit		CA070-A1	
Rated capacity	Cooling	kW	7.1
	Heating	kW	8
Electrical parameters	Power supply	Ph/V/Hz	1/220-240/50/60
Performance	Airflow	m³/h	1260/1070/820/680
	Sound power level	dB(A)	55
	Sound pressure level	dB(A)	36/33/29/26
Installation	Dimensions without packaging (W/D/H)	mm	840/840/204
	Dimensions with packaging (W/D/H)	mm	990/990/310
	Net/gross weight	kg	27/31
	Liquid pipe diameter	mm	9.52
	Gas pipe diameter	mm	15.88
	Controller	Wireless option	YR-HRC01
	Wired option	YR-C01	
Cover	Type	Option	PB-950HE4
	Dimensions without packaging (W/D/H)	mm	950/950/50
	Dimensions with packaging (W/D/H)	mm	1000/1000/110
	Net/gross weight	kg	6.5/9

