Mobile air conditioners

Compact appliances in sophisticated style, with 4 operating modes: cooling, heating, drying and air supply. The air conditioners are equipped with wheels and carrying handles for easy handling. The appliances are controlled with a advanced panel or a wireless controller.

Wireless controller included.



Full control

Filter cleaning notification (icon on the display) after 250 operating hours.



4 operating modes

Comprehensive application of the appliance for cooling, air supply, drying or heating.



Swing function

Shutter swinging for air distribution as needed.



Time

The air conditioner has the function to set the operation time. The operation of the appliance will start or end at the programmed time.













Indoor unit			AM12HEIA4
Power supply		f/V/Hz	1/220~240V/50 Hz
Cooling	Rated capacity	W	3400
	EER	W/W	2.6
	Rated power consumption	W	1300
	Rated current	A	5.80
Heating	Rated capacity	W	2 700
	COP	W/W	2.7
	Rated power consumption	W	1000
	Rated current	A	4.60
Maximum power input		W	1450
Maximum current		A	8.00
Starting current		A	/
Plug type		Α	16
Compressor	Model		DSM215V2UDZ
	Туре		Rotary
	Brand		GMCC
	Capacity	Btu/H	10918
	Input	W	985
Internal fan motor	Model		YDK15-6
	Brand		WELLING
	Input	W	52.5
	Capacitor	μF	1.5
	Speed (high/mid/low)	rpm	630/570/490
Internal airflow	(high/mid/low)	m³/h	390/360/330
Sound power level	(high/mid/low)	dB(A)	64/63.5/63
External fan motor	Model		YDK45-4
	Brand		WELLING
	Input	W	119
	Capacitor	μF	3.5
	Speed	rpm	1130
External airflow		m³/h	550
Unit dimensions	(WxHxD)	mm	476 x 710 x 385
Packaging dimensions	(WxHxD)	mm	545 x 885 x 435
Net/gross weight		kg	33.5/38.5
Refrigerant			R290